

SUMMA F SERIES

Professional flatbed finishing systems

00

F

Summa.com | #SummaFinish

ABOUT SUMMA

Summa is a manufacturer of innovative cutting equipment that helps companies and people to finish their applications to the highest standards. Delivering outstanding quality conforming these high standards, has secured the Summa reputation for legendary performance.

Companies from all over the world use Summa cutting solutions for products in the printing, signage, display, apparel and packaging industry. With the cutting solutions from Summa your business is futureproof for many years to come.

Summa.com | #SummaFinish



About Summa	02
Summa F Series	04
The Summa flatbed cutters are developed to grow with your b Enjoy the countless possibilities all in one machine.	usiness.
Base Unit	08
Multiple flatbed sizes are available to fulfill your cutting needs.	
Summa F1612	09
Summa F1432	10
Summa F1832	11
Summa F3220	12
Summa F3232	13
Modules & Tools	14
The extensive range of modules and tools allow you to finish variety of applications.	a wide

Tangential Module	16
Drag Module	21
Rotary Module	22
Standard Router Module	23
HF Router Module	24
Tool Application Overview	25
Media Handling & Workflows	28
Rely on efficiency with media handling and optimised workflows.	
Summa GoProduce Software	34
Powerful, in-house developed software tailored to the Summa F S	eries.
Technical Specifications	39
Order Codes	40

SUMMA F SERIES, BUILT TO GROW WITH YOUR BUSINESS

With the F Series, Summa offers a future-proof cutting product line based on over 30 years of expertise in building the world's very best cutting plotters. These advanced engineered flatbed cutting tables are designed to cut various sheet and rigid materials as well as roll stock. A multifunctional cutting head, a great range of modules and tools and many media handling options contribute to the series' versatility and flexibility.

Over the years, the Summa F Series opened many doors for our customers, enabling them to expand business into new markets such as packaging design, Point Of Sale and textile applications.

Complete F Series line-up

Applications

The F Series is designed to process a wide variety of materials for an even greater diversity of applications. Achieve a perfect cut with the Summa flatbed cutters to realise flawlessly finished end products.

S Sign & Display

The world of Sign and Display is broad and versatile. The flatbed cutting solutions can optimise your print & cut workflow, meet your customers' deadlines and deliver perfectly finished endproducts.

- POS displays
- Soft signage
- Stickers
- Mock-up designs
- Traffic Signs
- Billboards



When processing textiles, a most accurate cut is of key importance. With a great diversity in production processes, textile cutting is still often done manually. The flatbed cutters enable businesses to optimise their workflow, make it more efficient and significantly reduce material waste.

- Backlit displays
- Flags & banners
- Interior decoration
- Sportswear
- Fashion

😚 Packaging

In today's imaging dominated world the role of packaging is more relevant than ever. Packaging must, therefore, stand out and attract the eye of the beholder. At the same time, it is important packaging is strong enough to withstand transportation handling.

- Prototype packaging
- Customised packaging
- Short-run packaging
- Event-based packaging
- Creative packaging







SUMMA F SERIES

The F Series is developed to meet every customer's cutting need. For this reason, the flatbed cutters from Summa include so many elements to compose your ideal cutting solution.

F3220 w/ Heavy-Duty Roll Support

1

1

One Machine, Countless Possiblities

It starts with the base unit with a choice of no less than 5 models. Then you can carefully choose the modules and tools you need for your applications and consider the various media handling add-ons. Additionally, the included GoProduce software enables you to operate the cutter with ease and set up a productive workflow.

01 Base Unit		
02 Modules & Tools		
03 Media Handling Add-on		
04 Software		ě.
	4	F1612 w/ Conveyor Extension

Build your workhorse

The Summa F Series include a number of very powerful elements to combine into your ideal cutting solution. What's more, the available tools are retrofittable and add-ons and media handling options can be acquired at any stage. This is exactly what makes an F Series flatbed cutter the ideal workhorse to grow with your business.

01 | Strong Base Unit

The base unit is the foundation of a good performing cutting workflow. It has to be strong and the right size. With Summa you can choose from no less than 5 models. Also, the integrated safety system is part of the flatbed's strong foundations contributing to a safe working environment. Summa products are CSA and ISO 9001 certified to meet the highest standards for efficiency, quality improvement and high-end service.

- Flatbeds available in five sizes
- Easy maintenance of the system
- Complies with worldwide health and safety requirements
- Highly advanced technology
- Cutting table remains easily accessible
- Optimised footprint
- CSA Certified
- ISO 9001 Certified

02 | Extensive Range of Modules & Tools

The F Series perfectly grows in line with your business goals and aspirations. Open up to new markets and applications with the modules and tools of your choice. The multifunctional head is able to hold up to three modules at once, with the tools you prefer.

• Drag knife module • Tangential module

• High Torque Rotary module

- · Standard Router module
- High-Frequency Router module
- · Extensive choice of tools

03 | Efficient Media Handling & Workflows

The flatbed cutters are equipped with convenient media handling features and multiple add-ons to choose from. Further optimise your cutting workflow thanks to the operator zone, barcode workflow and F-Performance.

- Conveyor belt system
- Roll support system
- Vacuum table
- Media advance clamps
- Operator zone
- Poster trim
- Barcode workflow
- F-Performance
- And many more
- Exclusive F1612 Add-ons:
- Conveyor extension
- Basket
- Roll-up system
- **Extension Tables**

04 | Powerful Software

Summa GoProduce is a powerful and in-house developed software. The cornerstone of the good functioning of your F Series. Tailor and use the software as you wish through targeted features and choose the level of advancement according to your specific cutting requirements.

- Material manager
- Custom configuration of action sets
- Barcode functionality (Pro Pack)




Tangential Module

Summa GoProduce



Working area comparison



A STRONG BASE TO BUILD UPON

High-quality cutting equipment relies on a strong base. It requires a cutting unit which can be enhanced with additional features, options and add-ons at any given time. This way, the cutter can grow together with your business goals and aspirations. That is what the F Series is all about. Providing a solid base to transform your F Series model into the versatile cutting solution that perfectly fits your business needs.

The F Series is your versatile business companion. A companion you can build upon.

TIP | The following product sheet pages can be used or printed separately for your reference.

F1612 w/two Tangential Modules

SUMMA FI612

The F1612 is Summa's smallest F Series flatbed cutter, fitting effortlessly into many production area's. It represents the ideal cutting solution for sign makers who want to automate their cutting workflow or extend their cutting applications.

Key Benefits

- Small footprint
- Straightforward installation
- Media handling options
- Modular tooling system
- Integrated Safety System
- Future-proof

Ideal to cut:

- Cardboard material
- Roll stock
- (Technical) textile
- Synthetic material
- Foamboard
- Wood

Modules & Tools

All F Series models can be equipped and retrofitted with various modules and tools. This makes the F Series ideal to grow with your business and open up new markets at any given time.

- High-Frequency Router
- High Torque Rotary module
- Tangential module
- V-Cut tools, Creasing tools, Heavy-Duty Cutout tool, etc.





Legendary Performance



Summa website

Model	F1612
Dimensions	247 x 220 x 110 cm
Material width	Up to 165 cm
Work zone	160 x 120 cm
Vacuum	1.3 kW (50Hz) / 1.75 kW (60Hz)
Vacuum zones	Variable on the width of the machine
Requirements	Standard: 3 x 400V + N, 50Hz, max 20A Or: 3 x 208V + N, 60Hz, max 30A Or: 3 x 230V, 50Hz, max 20A
Standard solution includes:	 F Series flatbed system Conveyor system with pneumatic media clamps and roll support Security Pack Camera system Axis Control software Drag module ADC left & right GoProduce software Speed: up to1000 mm/sec Acceleration: up to 1G

Media Handling & Workflows

The flatbed cutter is standard equipped with a range of convenient media handling features. For the F 1612 model special media handling options are available to further enhance the use of this compact flatbed.

Enjoy an automated workflow and ease-of-use:

- Twin Workflow
- Operator Zone
- Poster Trim
- Barcode Workflow

Media Handling Add-Ons

- · Conveyor extension
- Roll-up system
- Extension tables
- Basket



SUMMA FI432

The F1432 is the latest addition to the F Series flatbed cutters. It allows to process popular 137 cm/54" roll widths more efficiently and its working length gives sufficient margin to easily cut 3m/10ft jobs. For many businesses, this size is the ideal interim solution between the F1612 and F1832 models.

Key Benefits

- Perfect interim size
- Modular tooling system
- Integrated Safety System
- Future-proof

Ideal to cut:

- Roll stock
- Lengthy materials
- Cardboard material
- (Technical) textile
- Synthetic material

Modules & Tools

All F Series models can be equipped and retrofitted with various modules and tools. This makes the F Series ideal to grow with your business and open up new markets at any given time.

- High Frequency Router
- High Torque Rotary module
- Tangential module
- V-Cut tools, creasing tools, Heavy-Duty Cutout tool, etc.





Legendary Performance



Summa website

Model	F1432
Dimensions	230 x 422 x 122 cm
Material width	Up to 142 cm
Work zone	136 x 320 cm
Vacuum	2.2 kW (50Hz) / 2.55 kW (60Hz)
Vacuum zones	6 zones (2 lines x 3 columns)
Requirements	Standard: 3 x 400V + N, 50Hz, max 30A Or: 3 x 208V + N, 60Hz, max 30A Or: 3 x 230V, 50Hz, max 20A
Standard solution includes:	 F Series flatbed system Conveyor system with pneumatic media clamps and roll support Security Pack Camera system Axis Control software Drag module ADC left & right GoProduce software Speed: up to1000 mm/sec Acceleration: up to 1G

Media Handling & Workflows

The flatbed cutter is standard equipped with a range of convenient media handling features. Enjoy an automated workflow and ease-of-use:

- Twin Workflow
- Operator Zone
- Poster Trim

- Barcode Workflow
- Tandem Mode



SUMMA F1832

The F1832 F Series flatbed cutter is a perfect match for cutting popular materials, such as 150 cm wide rolls and 152 x 304 cm rigid board materials. Combined with the High Torque rotary tool, the F1832 is ready to conquer also the textile market with the ability to cut the popular textile size of 183 cm.

Key Benefits

- Processes popular board and roll material
- Modular tooling system
- Integrated Safety System
- Future-proof

Ideal to cut:

- Cardboard material
- Roll stock
- (Technical) textile
- Synthetic material
- Foamboard
- Wood

Modules & Tools

All F Series models can be equipped and retrofitted with various modules and tools. This makes the F Series ideal to grow with your business and open up new markets at any given time.

- High Frequency Router
- High Torque Rotary module
- Tangential module
- V-Cut tools, creasing tools, Heavy-Duty Cutout tool, etc.





Legendary Performance



Summa website

Model	F1832			
Dimensions	279 x 422 x 122 cm			
Material width	Up to 190 cm			
Work zone	184 x 320 cm			
Vacuum	2 x 2.2 kW (50Hz) / 2 x 2.55 kW (60Hz)			
Vacuum zones	8 zones (2 lines x 4 columns)			
Requirements	Standard: 3 x 400V + N, 50Hz, max 30A Or: 3 x 208V + N, 60Hz, max 30A Or: 3 x 230V, 50Hz, max 20A			
Standard solution includes:	 F Series flatbed system Conveyor system with pneumatic media clamps and roll support Security Pack Camera system Axis Control software Drag module ADC left & right GoProduce software Speed: up to1000 mm/sec Acceleration: up to 1G 			

Media Handling & Workflows

The flatbed cutter is standard equipped with a range of convenient media handling features. Enjoy an automated workflow and ease-of-use:

· Barcode Workflow

• Tandem Mode

- Twin Workflow
- Operator Zone
- Poster Trim

Media Handling Add-on Available:

- Heavy-Duty Roll Support

SUMMA F3220

The F3220 F Series flatbed cutter has a working width of 3.2 m. It is the ideal companion to process wide-format materials with utmost ease and accuracy. Thanks to the size users are able to obtain a print & cut workflow fitting seamlessly into each other, opening up to endless applications for the textile market in particular.

Key Benefits

- Matches 3.2 m wide textile printers
- Ideal for high-production
 environments
- HD RS for heavy roll material
- Modular tooling system
- Integrated Safety System
- Future-proof

Ideal to cut:

- Textile (flags, mesh, banners)
- 3 m x 2 m board material

Modules & Tools

All F Series models can be equipped and retrofitted with various modules and tools. This makes the F Series ideal to grow with your business and open up new markets at any given time.

- High Frequency Router
- High Torque Rotary module
- Tangential module
- V-Cut tools, creasing tools, Heavy-Duty Cutout tool, etc.







Summa website

Model	F3220
Dimensions	422 x 313 x 122 cm
Material width	Up to 332 cm
Work zone	327 x 210 cm
Vacuum	4 kW (50Hz) / 4.6 kW (60Hz)
Vacuum zones	7 zones (1 lines x 7 columns)
Requirements	Standard: 3 x 400V + N, 50Hz, max 20A Or: 3 x 208V + N, 60Hz, max 30A Or: 3 x 230V, 50Hz, max 20A
Standard solution includes:	 F Series flatbed system Conveyor system with pneumatic media clamps and roll support Security Pack Camera system Axis Control software Drag module ADC left & right GoProduce software Speed: up to1000 mm/sec Acceleration: up to 1G

Media Handling & Workflows

The flatbed cutter is standard equipped with a range of convenient media handling features. Enjoy an automated workflow and ease-of-use:

- Twin Workflow
- Operator Zone
- Poster Trim
- Barcode Workflow

Media Handling Add-On Available:

Heavy-Duty Roll Support



SUMMA F3232

The F3232 is Summa's largeformat F Series flatbed cutter, the ideal companion to process popular print sizes with utmost ease and accuracy. The large working area enables a print & cut workflow fitting seamlessly into each other, opening up to endless applications for sign&display and textile market.

Key Benefits

- Matches 3.2 m wide textile printers
- Ideal for high-production
 environments
- HD RS for heavy roll material
- Modular tooling system
- Integrated Safety System
- Future-proof

Ideal to cut:

- Textile (flags, mesh, banners)
- 3 m x 2 m board material

Modules & Tools

All F Series models can be equipped and retrofitted with various modules and tools. This makes the F Series ideal to grow with your business and open up new markets at any given time.

- High Frequency Router
- High Torque Rotary module
- Tangential module
- V-Cut tools, creasing tools, Heavy-Duty Cutout tool, etc.





Legendary Performance



Summa website

Model	F3232
Dimensions	422 x 422 x 122 cm
Material width	Up to 332 cm
Work zone	327 x 320 cm
Vacuum	2 x 2.2 kW (50Hz) / 2 x 2.55 kW (60Hz)
Vacuum zones	14 zones (2 lines x 7 columns)
Requirements	Standard: 3 x 400V + N, 50Hz, max 20A Or: 3 x 208V + N, 60Hz, max 30A Or: 3 x 230V, 50Hz, max 20A
Standard solution includes:	 F Series flatbed system Conveyor system with pneumatic media clamps and roll support Security Pack Camera system Axis Control software Drag module ADC left & right GoProduce software Speed: up to1000 mm/sec Acceleration: up to 1G

Media Handling & Workflows

The flatbed cutter is standard equipped with a range of convenient media handling features. Enjoy an automated workflow and ease-of-use:

Poster Trim

Barcode Workflow

- Twin Workflow
- Operator Zone
- Tandem Mode

Media Handling Add-On Available:

• Heavy-Duty Roll Support



MODULES & TOOLS

The F Series models are equipped with a **multi-functional cutting head** that is able to hold up to three cutting modules at once. The system is therefore able to efficiently process cutting jobs including multiple cutting techniques. Or to quickly switch between jobs in which different materials are used. The LED pointer in the central unit and integrated camera system enable fast and accurate mark recognition.



Extensive range of Modules & Tools

Summa offers an extensive range of modules and tools to choose from. Choose what cutting modules you need based on the products you produce or will produce in the future. Start with the basics or discover the more advanced options with the Tangential cutting module.

Tangential Module for:

- Adhesive vinyl
- Window film
- Magnetic material
- Reflective sheeting
- Foamboard with paper

Router Module for:

- Corrugated PP board
- Expanded PVC board
- Polycarbonate
- ACP/ACM

Rotary Module for:

- Uncoated woven polyester
- Coated woven polyester
- Packaging foam

Drag Module for:

- Paper
- · Adhesive vinyl

Knives, Blades & Bits

your company grows.

- · Adhesive PVC banner vinyl
- Cardboard
- Polypropelene
- Polycarbonate
- Sandblast material
- MDF
- Foamcore with HIPS liner
- Plexi
- Technical textiles



Router Module

Tangential Module





Video: ADC

Drag Module

Automated Depth Control | ADC

recognition and parameter pre-sets.

The Automated Depth Control (ADC) simplifies tool, knife or bit changes significantly. The ADC measures the tip of the knife or bit accurately and sets the down position of the tool to the table's level, thus guaranteeing a flawless cut.

Benefits

- · Easy tool change
- Automatic depth measuring
- Flawless cutting
- · Less operator intervention
- Saving valuable time







- Adhesive PVC Banner Vinyl

Each of the above modules can house different tools, blades and bits. Choose the tool you need to cut your specific material and obtain the best cutting quality. All tools include a barcode ID, ensuring automatic

You can extend your tool gamut whenever you see fit as

- · Synthetic textiles

TANGENTIALMODULE | [6

TANGENTIAL MODULE

The powerful Tangential Module offers a vertical force of 10 kg and corresponds to a wide range of matching tools enabling users to process an abundance of applications. Each of the many and varied tools has a barcode ID, which ensures automatic recognition and parameter settings.

Thanks to the multi-functional head on the F Series, users are able to install up to three modules. This way, multiple jobs with different cutting techniques can be assigned to a single machine, such as creasing and cutting, without the need to remove modules.

The wide range of tools is yours to choose from





Kiss-Cut Tool

Clean cuts for easy weeding

Single Edge Cutout Tool

Cuts materials up to 6 mm thick

Double Edge Cutout Tool

• Ideal to cut rigid material

Heavy-Duty Cutout Tool

Cuts material up to 15 mm thick

Creasing Tools

· Clean creases without tearing

V-Cut Tools

• Precise angle adjustments

Perforating Tool NEW

• Efficient and fast perforations

Electronic Oscillating Tool

• High processing speeds

Pneumatic Oscillating Tool

• High-performance cutting tool

Pneumatic Oscillating Tool-L

• Thick and soft materials

With mechanically-controlled knife pressure, this tool is specifically designed for kiss-cutting material down to its liner up to 1.2 mm thick. This tool also includes an adjustable nose piece for precise depth control.

Blades

Strongest features

- · Precise depth control
- · Clean cuts for easy weeding
- Cuts a wide variety of vinyl and film

Ideal for cutting:

- Paper < 200g
- · Adhesive vinyl
- · Sandblast material
- Window film
- Magnetic material
- Adhesive PVC Banner material

390-551 - Tangential Double Tip Knife 36° Max cutting thickness - 0.25 mm

390-534 - Tangential Knife 36°

Max cutting thickness - 0.25 mm

390-550 - Tangential Knife 60° Max cutting thickness - 1.2 mm

 \rightarrow 390-560 - Tangential Knife 45° wedge 40/25° Max cutting thickness - 1 mm





Single Edge Cutout Tool

The Single Edge Cutout Tool is designed for detailed cutting through materials up to 6 mm thick. A spring-loaded gliding disk allows cutting of very precise details and can be fixed at a set depth.

Strongest features

- Precise cutting of details
- Cuts material up to 6 mm thick
- · Fixed depth setting

Ideal for cutting:

- Paper < 200 gr
- Cardboard 300-500 gr
- · Adhesive vinyl
- Foamboard <= 2 mm
- Polypropelene <= 1.2 mm
- Polycarbonate <= 0.6 mm
- Adhesive PVC
- · Magnetic material



500-9801 - Single Edge Cutout Knife 65° Max cutting thickness (with gliding disk) - 6 mm Max cutting thickness (without gliding disk) - 6 mm







S 🖗



S

The Double Edge Cutout Tool ensures minimal wear when cutting through rigid material up to 5 mm thick. Here also, a spring-loaded gliding disk allows cutting of very precise details and can be fixed at a set depth.

Strongest features

- · Precise cutting of details
- Cuts at both knife sides
- Minimal knife wear
- Ideal to cut rigid material

Ideal for cutting:

- Paper < 200 gr
- Cardboard 300-500 gr
- Adhesive vinyl
- Adhesive PVC
- PVC Banner
- Reflective sheeting
- Expanded PVC board <= 1.2 mm
- Polypropelene <= 1.2 mm
- Polycarbonate <= 0.6 mm
- Magnetic material

Blades



500-9802 - Double Edge Cutout Knife 50° Max cutting thickness (with gliding disk) - 3 mm Max cutting thickness (without gliding disk) - 3 mm



500-9803 - Double Edge Cutout Knife 60° Max cutting thickness (with gliding disk) - 5 mm Max cutting thickness (without gliding disk) - 5 mm

500-9804 - Double Edge Cutout Knife 50° Burr-Free

Max cutting thickness (with gliding disk) - 3 mm Max cutting thickness (without gliding disk) - 3 mm



S 🖗

Heavy-Duty Cutout Tool

The Heavy-Duty Cutout Tool is suitable for cutting through thicker materials up to 15 mm thick.

Strongest features

· Ideal to cut very thick material

Ideal for cutting:

- Cardboard 300-500 gr
- Adhesive vinyl
- Adhesive PVC
- PVC Banner
- Corrugated PP board <= 5 mm
- Expanded PVC board <= 1.2 mm
- Polypropelene <= 1.2 mm
- Polycarbonate <= 0.6 mm
- Foamcore with paper liner <= 5 mm
- · Varnish blankets

Blades

500-9807 - Heavy-Duty Cutout Knife 45° - 90 ° Max cutting thickness - 15 mm

S









Creasing Tools


Several creasing wheels, designed in different depths and radius sizes, are available for creasing and scoring paper, cartons, polypropylene and PVC material.

Strongest features

- · Clean creases without tearing
- · Directional pressure adjustments

Ideal for creasing:

- Corrugated B-C-A-EE-BC flute (3 - 6 mm)
- Corrugated C Flute (4 mm)
- Corrugated E Flute (1.5 mm)
- Paper < 200gr
- Cardboard 300 500 gr m2
- Polypropelene sheets <= 1.2 mm
- Corrugated B-C-A-EE-BC flute (3-6mm)



D25 R3 W8

500-9326 i









R

500-9328 |

- 2pt

1pt





V-Cut Tools

The V-Cut Tools are available in 5 angles and are designed to cut a V-shaped groove in rigid sandwich and foam composite boards up to 27 mm thick, depending on the material's density.


Strongest features

- Precise angle adjustment
- Very fast blade changes

Ideal for cutting:

- · Honeycomb board
- Foamcore with paper liner

Blades



500-9826 - V-Cut Hard Metal Max cutting thickness 18-27 mm

Line up V-Cut tools



Perforating Tool NEW

The new Summa perforating tool for the F Series is used to make perforations in a very efficient and fast way. By using this tool, the perforated materials will be a lot easier to bend or fold. Then, the folds will have sharper 90° edges resulting in a nicer finish. This will save considerable time in the assembling of, for instance, cardboard or polypropylene boxes.

Strongest features

- Up to 25 times faster cutting of perforation lines (versus EOT tool)
- · Alternative for creasing. Folding and bending lines into cardboard

- · High-quality perforated cuts
- Several knives available

Ideal for cutting:

- Solid cardboard
- Corrugated board
- Polypropylene film

Knives

500-9890 | Perforation Knife 1 x 1 mm D 1.1 mm

500-9892 | Perforation Knife 3 x 3 mm D 4 mm 500-9891 | Perforation Knife 1.7 x 1.7 mm D 1.1 mm 500-9893 | Perforation Knife 5 x 5 mm D 4 mm

Electronic Oscillating Tool | EOT

mmm

S 🟵

Ideal for cutting soft and medium density materials such as corrugated board and foam up to 18 mm thick. The Electronic Oscillating Tool is driven by an electric motor, producing up to 12,000 rpm and moves a knife up and down over a stroke of 1 mm.

Strongest features

- Powerful cutting tool
- High processing speeds
- Low maintenance

Ideal for cutting:

- Corrugated B-C-E Flute (1.5-4 mm)
- Foamcore with paper liner
 <= 10 mm
- Foamcore with paper liner > 5 mm
- Honeycomb board < 10 mm
- Gasket

500-9815 -EOT L33 Knife 45°-85°

Max cutting thickness (with gliding disk) - 13 mm Max cutting thickness (without gliding disk) - 19 mm

500-9814 -EOT L38 Knife 45°-86°

Max cutting thickness (with gliding disk) - 18 mm Max cutting thickness (without gliding disk) - 24 mm

Blades

500-9800 - EOT L25 Knife 65° Max cutting thickness (with gliding disk) - 5 mm Max cutting thickness (without gliding disk) - 5 mm

500-9810 - EOT L25 Knife 65° - 80° Max cutting thickness (with gliding disk) - 5 mm

Max cutting thickness (with gliding disk) - 5 min Max cutting thickness (without gliding disk) - 11 mm

500-9811 - EOT L25 Knife 65° - 85° Max cutting thickness (with gliding disk) - 5 mm Max cutting thickness (without gliding disk) - 11 mm

500-9813 - EOT L25 Knife 0°-75° Max cutting thickness (with gliding disk) - 5 mm Max cutting thickness (without gliding disk) - 6 mm

500-9812 - EOT L28 Knife 65° - 85°

Max cutting thickness (with gliding disk) - 8 mm Max cutting thickness (without gliding disk) - 14 mm









The standard Pneumatic Oscillating Tool, powered by compressed air, moves its knife up and down over a stroke of 8 mm. The robust construction of the tool makes it suitable to cut thick material, such as honeycomb board, corrugated board and foam board.

Strongest features

- High-performance cutting tool
- High processing speeds
- Availability of longer knife

Ideal for cutting:

- Triple walled cardboard
- Double walled cardboard
- Packaging Foam
- Honeycomb board >= 10 mm
- Foamcore with paper liner> 5 mm
- Re-board®
- Foamboard with plastic
- Rubber



500-9830 - POT Knife Flat Point L20 T0.63 Max cutting thickness - 18 mm

S

500-9831 - POT Knife Flat Point L27 T0.63 Max cutting thickness - 25 mm





500-9833 - POT Knife Serrated L27 T1.0 Max cutting thickness - 25 mm

500-9834 - POT Knife Point L20 T1.0* Max cutting thickness - 16 mm *Extra protective mat recommended





Pneumatic Oscillating Tool - Long | POT-L

The Pneumatic Oscillating Tool-L (POT-L) is an addition to the standard POT and is used with a Longer type of knife. The POT-L is able to process thick, soft foams with a maximum thickness up to 42 mm. The robust construction of the tool makes it suitable to cut thick material, such as honeycomb board, corrugated board and foam board.

Strongest features

- High-performance cutting tool
- High processing speeds
- · Availability of longer knife

Ideal for cutting:

- Triple walled cardboard
- Double walled cardboard
- · Packaging Foam
- Honeycomb board >= 10 mm
- Foamcore with paper liner> 5 mm
- Re-board®
- · Foamboard with plastic
- Rubber

Blades

500-9835 - POT-L Knife L50 T1.0* Max cutting thickness - 42 mm *POT-L Tool Only







DRAG MODULE

The Drag Module enables users to make notations with pens or to kiss-cut materials with a pressure of 600 grams of downforce, using a drag knife.

Multiple Drag Modules can be mounted into the multi-functional head of the flatbed to allow both kiss-cutting and drawing without the need to change modules.

The Drag Module is standard included with all F Series models. The perfect module to start with!

Ideal for cutting:

- Paper < 200g
- · Adhesive vinyl
- Sandblast material
- Window film

Drag Knife Tool

With 600 g of force, this tool is ideal for kiss-cutting a wide range of adhesive vinyls.

Strongest features

- · Fast and precise
- · Pinpoint kiss-cutting for easy weeding

391-231 - Drag Knife - 60° Max cutting thickness - 0.6 mm **391-358 - Drag Knife - 55°** Max cutting thickness - 0.8 mm

 \supset

> T

391-360 - Standard Knife 36° Max cutting thickness - 0.25 mm

Pen Tool & Universal Pen Holder Tool

The pen tool allows precise drawing on various materials, using either our own brand of fiber tip pens or a variety of third-party pencils and pens in a multitude of sizes and diameters.

Strongest features

· Precise drawing on various material types

Pens



MP06BK Fibre Tip Pen - Black







 Universal
 Pen
 Holder
 /
 Copper

 accepts
 pen/pencils
 from
 9.5
 mm

 to 11 mm in diameter



ROTARY MODULE

The High Torque Rotary Module is driven by an electronic motor and is capable of handling all kinds of textiles. Thanks to extra rotational power, the HT RM is also able to cut tougher and thicker substrates, such as banner material.

Ideal for cutting:

- Uncoated woven polyester
- Coated woven polyester
- Laminated fabrics
- Canvas
- Fleece
- Felt
- Packaging foam
- Synthetic textiles
- Technical textiles





Take the production of your textile applications to the next level with the High Torque Rotary Module.

In general, the vacuum table of the F Series flatbed cutter has less grip on textiles. However, with the High Torque Rotary Module the material will stay in place thanks to the minimal horizontal force it produces. Consequently, also extremely porous material can easily be processed with the HT RM.









Decagonal Knives

Strongest features

· Rotary blade reduces drag on material · Motor-driven blade for reliable cutting • Clean, precise cuts of all textile types



500 9860 Decagonal D25 Knife Max cutting thickness - 1.5 mm



500 9861 Decagonal Knife D28 Max cutting thickness - 3 mm



500 9862 Decagonal Knife D32 Max cutting thickness - 5 mm

STANDARD ROUTER MODULE

The Standard Routing Module is available in two different power ratings and can handle most solid boards in the graphic and sign industry. Hard foam PVC, acrylic and aluminium covered foam boards as well as other materials, such as wood and MDF can be processed.

Power options:

- 1000W
- 1400W

Ideal for cutting:

- Expanded PVC board
- Corrugated PP Board
- Polycarbonate
- MDF
- Plexi
- ACP/ACM
- Foamcore with PVC liner
- Foamcore with HIPS liner

If you aspire to grow your business, you have to be ready to take on any job. Whether this means cutting 1.000 magnetic stickers, promotional board material for an upcoming sale, signage cutout of plexi or MDF, you need a system that is cut out for any job, each time again. With the standard router module, you will extend your cutting solutions considerably. The higher power on the 1400W router will even allow to process materials more than 30% faster than the 1000W router.

Strongest features

- Allows routing, engraving & polishing
- Processes a wide range of substrates
- Efficient dust extraction for clean operation (optional vacuum cleaning kit)
- Excellent edge finishing
- · Availability of various bits

Routing Bits

500-9850 - Routing Bit D3/3 L38/11 1Fl UC

500-9863 - Routing Bit D6/10 L50 90° B 2FL

Go to: Summa Router bits overview



500-9852 - Routing Bit D4/4 L50/12 1Fl UC

500-9864 - Routing Bit D6/6 L50/22 2FL UC/DC





HF ROUTER MODULE

The HF Routing Module is equipped with a high-frequency spindle and a higher power output, which allow higher processing speeds. The utmost balanced, highfrequency spindle provides for a much smoother finishing of rigid substrates. The bit is pneumatically controlled and can be replaced manually in a fast and simple way.

Ideal for cutting:

- Expanded PVC board
- Corrugated PP Board
- Polycarbonate
- MDF
- Plywood
- Natural Hardwood
- Plexi
- ACP/ACM
- Foamcore with PVC liner
- Foamcore with HIPS liner

Especially for high-production environments, the High Frequency Router module will proof its worth. So, if you process tough, rigid material types on a regular basis and you want the job to be done rapidly and efficiently, the HF router is your first choice tool. Achieve exceptional performance and productivity with the high-frequency spindle and deliver top-quality products with impeccable edge finishing.



Strongest features

- Maximises productivity
- Higher processing speeds
- Robust, reliable construction
- Impeccable edge finishing
- Efficient dust extraction for clean operation (optional vacuum cleaning kit)
- · Availability of various bits

500-9857 - HF Routing Bit D6/6 L50/12 MP 1FI UC BAL

500-9858 - HF Routing Bit D6/6 L58/22 MP 1FI UC BAL

alle a



Routing Bits

500-9854 - HF Routing Bit D6/3 L50/06 MP 1Fl UC

500-9856 - HF Routing Bit D6/4 L50/12 MP 1Fl UC

500-9859 - HF Routing Bit D6/6 L50/14 POLISHING

Go to: Summa Router bits overview



HF ROUTER MODULE | 25

Video: HF Router



Tools | Application Overview

									Tonoontie	Madula				
			Jule				1	1	Tangentia	ai Module				_
	Drag Module	Standard Routing Module	HF Routing Module	High Torque Rotary Module	Kiss Cut Tool + 390-534 knife	Kiss Cut Tool+ 390-560 knife	Kiss Cut Tool + 390-550 knife	Single Edge Cutout Tool 500-9312	Double Edge Cutout Tool 500-931	Heavy Duty Cutout Tool 500-9314	EOT Tool 500-9320	POT Tool 500-9350	POT-L Tool 500-9358	Perforating Tool 500-9315
Recommended	¶ D€	utin	Roi	jh T tary	2-5.	s C 7-5	S C -5	igle tout D-9	uble tout D-9:	avy tout D-9	л Т 0-9	Т Т D-9.	1-L 0-9.	for. 0-9.
Alternative	Dra	Sta Roi	벞	Hig Rot	Kis 39(Kis 39(Kis 39(Sin Cut 50	Doi Cut 50	He: Cut 50(50.	50(50(Per 50
CARDBOARD MATERIALS														
Paper < 200 gsm														
Cardboard 300-500 gsm														
Corrugated B flute (3 mm)														
Corrugated C flute (4 mm)														
Corrugated BC flute (7 mm)														
Corrugated E flute (1.5 mm)														
Honeycomb board < 10 mm														
Honeycomb board >= 10 mm													*	
ROLL MATERIALS														
Adhesive vinyl														
Adhesive PVC banner vinyl														
PVC Banner														
Mesh Banner														
Sandblast material														
Reflective sheeting														
Window film														
Magnetic														
SYNTHETIC MATERIALS				1			1							
Corrugated PP board <= 5 mm														
Corrugated PP board > 5 mm														
Expanded PVC board <= 2 mm														
Expanded PVC board > 2 mm														
Polypropylene sheets <= 1.2 mm														
Polycarbonate <= 0.6 mm														
Polycarbonate > 1 mm														
Plexi														
PET < 1.2 mm														
PET < 2 mm														
COMPOSITES		11		I			1	I						
Foamcore with paper liner														
Foamcore with HIPS liner														
Foamcore with PVC liner														
ACP/ACM														
WOOD								1						
MDF														
Plywood														
Natural Hardwood														
TEXTILES	L													
Uncoated woven polyester														
Coated woven polyester														
Laminated Fabrics														
Canvas														<u> </u>
INDUSTRIAL MATERIALS								1	1	ļ				1
Varnish blankets														
Gasket														
Insulation foam													*	
Textiles (Coated-Uncoated)	<u> </u>													
Rubber	<u> </u>												*	
	* min	thickness	5 20 mm	1			1	I	1					1
		CITERIESS	, 20 11111				-							

		°	2.5°	å	°		_	1.5	8 0.7	_	_
	° o o	1 1	0 22	ol 30	0 45 4 45	T00 V8 5	Too 5 W8 6	T00 75 W	Too 35 W 9328	Too Too Pt	4 Too
Recommended	V-Cut Tool 0° 500-9340	V-Cut Tool 15° 500-9341	V-Cut Tool 22.5 500-9342	V-Cut Tool 30° 500-9343	V-Cut Tool 45° 500-9344	Creasing Tool D25 R3 W8 500-9325	Creasing Tool D25 R1.5 W8 500-9326	Creasing Tool D25 R0.75 W1.5 500-9327	Creasing Tool D15 R0.35 W0.7 2pt 500-9328	Creasing Tool D15 R0.17 W0.35 1pt 500-9329	Creasing Tool D50 R1.5 500-9324
Alternative	2-C	V-C	V-C	V-C	V-C	Crea D25 500	Crea D25 500	Crea D25 500	Crea D15 2pt	Crea D15 W0.	Crea D50 500
CARDBOARD MATERIALS											
Paper < 200 gsm											
Cardboard 300-500 gsm											
Corrugated B flute (3 mm)											
Corrugated C flute (4 mm)											
Corrugated BC flute (7 mm)											
Corrugated E flute (1.5 mm)											
Honeycomb board < 10 mm											
Honeycomb board >= 10 mm											
ROLL MATERIALS							I		1		
Adhesive vinyl											
Adhesive PVC banner vinyl											
PVC Banner											
Mesh Banner											
Sandblast material											
Reflective sheeting											
Window film											
Magnetic											
SYNTHETIC MATERIALS	1						1				
Corrugated PP board <= 5 mm											
Corrugated PP board > 5 mm											
Expanded PVC board <= 2 mm											
Expanded PVC board > 2 mm											
Polypropylene sheets <= 1.2 mm											
Polycarbonate <= 0.6 mm											
Polycarbonate > 1 mm											
Plexi											
PET < 1.2 mm											
PET < 2 mm											
COMPOSITES									1		
Foamcore with paper liner											
Foamcore with HIPS liner											
Foamcore with PVC liner											
ACP/ACM											
WOOD											
MDF											
Plywood											
Natural Hardwood											
TEXTILES											
Uncoated woven polyester											
Coated woven polyester											
Laminated Fabrics											
Canvas											
INDUSTRIAL MATERIALS											
Varnish blankets											
Gasket											
Insulation foam											
Textiles (Coated-Uncoated)											
Rubber											

MEDIA HANDLING & WORKFLOWS

The Summa F Series flatbed systems offer many intelligent and efficient media handling features to optimise and future-proof your cutting workflow. A number of them are integrated, others can be retrofitted at any given time.

So, go ahead and add another shift to your F Series operation with our large gamut of media handling add-ons and options to obtain ultimate production efficiency, reduce operator intervention and enhance overall ease-of-use.

Enhanced productivity with efficient media handling

The F Series flatbed cutters are equipped with a range of media handling features that are standard included with each model. Also a range of model-specific media handling add-ons is available to further enhance operator convenience and productivity. You can find a detailed overview of the specific media handling possibilities per model in the product sheets.

1. Conveyor System

The Conveyor System allows you to cut, crease and annotate large lengths of (flexible) material to large production runs. The conveyor automatically transports cut parts away from the cutting area. This allows the production of jobs that are longer than the actual working area of the flatbed cutter.

2. Media Advance Clamps

Pneumatically-driven media advance clamps fix the material while pulling it forward to work continuously in panels or while processing multiple jobs.


3. Roll Support System

In combination with the Conveyor System and the Media Advanced Clamps, the Roll Support System is ideal for processing roll material on all the Summa F Series models.

4. Vacuum Table

The vacuum table generates holddown force to keep the material in place during the cutting process while the selector adjusts the vacuum automatically to match the working area.

The vacuum table can be set up with zones that can be turned on or off in case you want to process smaller jobs.



A workflow to anyone's need

The F Series flatbed cutters allow to streamline the cutting workflow to your specific business needs. The different available workflows contribute to the flatbed's ease-of-use, minimise operator intervention and increase yield considerably. The below workflows are standard included with all F Series models, unless otherwise specified.



Operator Zone

With this feature the F Series' working area can be divided into two separate zones, a cut only zone and an Operator Zone. The included Conveyor system automatically feeds all cut material forward to the Operator zone. The cutting head doesn't move any further than the cut only zone, so the operator has access to the cut pieces safely at the front of the machine.



Poster Trim

This feature enables a fast cutting of posters without the need of importing any cutting data. The F Series built-in camera system automatically detects the edges of black printed frames and starts to cut immediately, without operator intervention. The Poster Trim functionality is the ideal way to make sure your posters are cut rapidly and precisely with a minimum of manual actions.

Videos:

Zone



Tandem Mode for F1432, F1832, F3232

By using the front zones and rear zones alternately, this feature leads to significant production increase. With the Tandem Mode, the active working area on the flatbed can be divided into front and back processing areas, enabling the user to load and unload material on one end of the table while cutting material on the other end of the table. This will avoid idle periods during cutting, which will add significant value to the overall workflow.



Poster Trim



Twin Workflow

To maximise productivity and flexibility in your finishing workflow, you can use the Twin Workflow. The Twin workflow combines the strength of a Summa roll cutter with an F Series flatbed cutter, meaning you can kisscut on the roll cutter and cut through on the F Series flatbed cutter.

The Twin Workflow has been developed for users that want to optimise the use of their equipment in a most efficient way. By using one of these workflows, productivity and performance will be brought to a higher level. The smooth integration of the cutters into existing workflows will further contribute to the customer's Productivity, Performance and Profitability! Operator



Tandem Mode



Twin Workflow



Certain RIP (Raster Image Processing) software offer the possibility to print a barcode with OPOS marks. This barcode can be used to identify the job and to automatically obtain the necessary cut data from the computer. Summa offers two possible ways to scan in a job.

With the Summa F Series built-in camera

With this F Series' optional barcode setup, scanning the job happens automatically and continuously by the built-in camera. The operator doesn't need to locate the job himself anymore. The job will be opened automatically in GoProduce to be processed immediately.

The greatest asset of Summa's revolutionary camera system is that the camera will search for the next job without operator intervention.

With a hand scanner

Another means to offer flexibility to the operator's workflow is scanning the job manually with a hand scanner.

This way the operator can easily switch between jobs and materials. Multiple, different jobs can be processed back to back with ease.


This feature is embedded in the GoProduce software. However, the hand scanner itself is not included and needs to be purchased separately.

Activation

The barcode workflow is included in the GoProduce Pro Pack software.

Video: Barcode Workflow





Barcode Workflow with Summa's built-in camera



Barcode Workflow with hand scanner

F-Performance

The F-Performance mode ensures an increase of up to **40%** of the F Series' performance. Advantages include faster up, down and turning movements of the cutting head, which will be most remarkable when using the Kiss-cut tool. Also, feeding material will happen significantly faster. The job will be finished practically twice as fast without compromising an inch on quality.

The F-Performance mode is available as free unlock on new machines via www.Summa.com/f-performance and as payable unlock on older F Series models, built before 2018.

Video: F-Performance "The usage of the F-Performance mode on the F1612 made a huge difference to our production speed. The small gains on feed speed and tool movement really add up to give us around **30%** additional productivity on this particular project."

/ Freestyle Design about F-Performance "

Workflow Compatibility

The Workflow Compatibility of the Summa GoProduce software ensures a seamless fit into existing workflows. The software offers flexible data import and is supported by the following RIP manufacturers:


RIP manufacturers: Agfa Asanti Cadlink RIP Caldera RIP ColorGATE RIP ErgoSoft PosterPrint ErgoSoft TexPrint GMG Production Suite ONYX RIP Wasatch RIP SAI- FLEXI		ging Software atibility: r
1. Prepare design	2. Print & setup	3. Finish
		F SERIES"

Testimonial | TrafficSupply

"WITH THE FI612 FLATBED CUTTER, THE JOB IS DONE IN AN INSTANT."

Company: TrafficSupply Core business: Traffic signs Challenge: Keep up with demand Solution: Summa F1612 **The Story |** A typical F1612 workflow starts with a simultaneous setup of the print and cut file. As soon as the printing and lamination part is finished, the roll with reflective foil is placed onto the roll-up system. Then advanced by the conveyor onto the F1612 flatbed cutter surface.

Subsequently, the cutter reads the barcode printed on the design and starts processing the correct file. By scanning the registration marks the cutter knows exactly how the roll is positioned onto the table – compensates if necessary – and starts to cut. Fast and efficiently.





Basket

The Basket is a handy accessory to reduce the media handling time, thus optimising your workflow. The F1612 can automatically process several feet of material while the basket is capturing the cut-out vinyl and/or waste material. Rely on an efficient cutting workflow and a clean work environment.

Extension Tables for Continuous Sheet Feed



The sturdy, foldable Extension Tables can be placed in front and at the back of the F1612. They are adjustable to set the correct height. This way, board material longer than the F1612 working area can still be processed. With the extension tables you can use the Continuous Sheet Feed feature, this enables the user to load and unload material while cutting. The feature helps to avoid idle periods during the processing of material and thus adds significant value to the overall workflow.

Roll-Up System



When kiss-cutting, the roll-up system winds the material back on a roll after it has been cut. This allows the F1612 to work unattended, while keeping the work area neat and clean. When cutting through, a workflow can be set up in combination with the basket or extension table. The roll-up takes care of the waste matrix while the operator collects the cutout material. The winded roll is also easily accessible for trolleys or other tools to handle heavy rolls.





Media Handling Add-on for F1832, F3220, F3232

Thanks to the conveyor extension, the F1612 makes light work of cut designs, that are much larger than their actual cutting area. Once the first part of the job is completed, the conveyor feeds the cut material to the extended front where it can be removed easily and safely, while the machine is cutting the next part. This minimises downtime considerably. *Note: All existing F1612 units in the field can be upgraded with this option.*

Videos:

Continuous Sheet Feed



Conveyor Extension



Heavy-Duty Roll Support



Heavy-Duty Roll Support

The Heavy-Duty Roll Support can be used on our wideformat flatbed sizes to allow a straight and effortless throughput of heavy print rolls before cutting the material. Especially for the processing of heavy banner material, non-stretchable wide textile rolls and lightly stretchable materials, the HD RS will prove its worth. It will even allow the processing of rolls up to 200 kg with ease.

G SUMMA IN-HOUSE DEVELOPED SOFTWARE

The Summa GoSuite software platform has been developed in-house to enable users to make the most of their print and cut workflow. With the Summa software, operators, designers and business owners, can easily process and analyse complex and high volume jobs with great flexibility.

Rely on powerful software to maximise the use of your Summa cutting equipment.

₹ 8 4

Summa GoProduce™

The user-friendly GoProduce software is part of Summa's GoSuite platform. GoProduce is developed for the operator of the F Series, handling jobs in a straightforward and easy way. The modern interface with improved navigation enables users to find and operate functions as quickly and intuitively as possible.

- Modern interface
- Improved navigation
- Quick and intuitive
- Windows-based
- Standard included
- Pro Pack available
- 30-day Trial available

Key Features (standard included)

Material Manager

The material database includes an extensive range of material types which settings can be adapted to your specific needs. Through methods, you only need to choose the material you want to process. Then, the material manager automatically chooses the correct tool and its settings for the cutting job.

Overcut Compensation

This GoProduce functionality avoids or minimises overcuts in the corners.

Sorting

The order in which objects are handled is important to minimise output time. GoProduce can determine the start and end of a vector and the order of processing. The aim here is to shorten the traverse path. Basic sorting is done by GoProduce itself.

Milling

With the interactive milling function, any change in tool diameter and rotation is performed immediately and shown on the working area. All milling paths are automatically created and displayed; the tool diameter is taken into account.

Camera Recognition

The recognition process and localisation of the registration marks can be tracked in the camera preview window. All kinds of compensations and marks, which occur in everyday practice, are manageable with GoProduce.

Back Side Cutting IMPROVED

Back side cutting is especially useful when cutting cardboard boxes in order not to damage the print and in order to ensure the print is located at the outside.

How to get started

Choose the functionalities you need and discover the software with a free 30-day trial on our website.

Knowledge Base:

Frequently asked questions have been bundled and answered by Summa experts in a knowledge database. Gradually, we will be extending the database with more tutorials, service-related topics and useful tips&tricks. Go to: www.summa.com/faq or scan the QR code.

Also, various tutorials are created to support you in the installation and use of Summa GoProduce.

TIP | Scan the QR code to watch all GoProduce tutorials on Summa's Youtube page.

Website:

Free 30-day trial



Videos:

Back Side Cutting



FAQ



GoProduce Tutorials





The optional GoProduce Pro Pack offers you advanced features such as barcode functionality, hot folder support, Twin Workflow and import possibility of plot files. Similar to the standard GoProduce software, also the Pro Pack will be gradually expanded with new functionalities.

Hot folder support

GoProduce could already import jobs by file selection by means of a hand scanner or OPOS barcode. With the hot folder functionality in GoProduce 2.0, files dropped in a folder can now be opened automatically in GoProduce.

Twin X - Import of plot files

Twin X enables GoProduce to read cutting files prepared for Summa Roll cutters. This way the Twin workflow, previously only available on OPOS CAM roll cutter units - can now also be used on all Summa roll cutter units, equipped with an OPOS X sensor.

Barcode functionality

The previous GoProduce barcode option is no longer available and is now converted to the Pro Pack.

GoProduce 2.0	GoProduce 2.0 Pro Pack
Standard available on www.Summa.com	One-time Pro version purchase (395-995)
Custom configuration of action sets	Custom configuration of action sets
Registration of square / round marks	Registration of square / round marks
Material manager	Material manager
Job log functionality	Job log functionality
Cut-off between jobs	Cut-off between jobs
Tool priority selector	Tool priority selector
Remote controller	Remote controller
Weedbox functionality	Weedbox functionality
Back side cutting edge-detection	Back side cutting edge-detection
	Barcode functionality
	Hot folder support
	Twin X - Import plot files



PLM Packlib: Summa's packaging library

The PLM Packlib* for Summa is a library of resizable standard packaging models. The most popular packaging standards FEFCO (corrugated cardboard) and ECMA (folding carton) are included. Also a few POS display designs and solid cardboards (furniture) designs are available.

Box/design dimensions and material thickness are parametric. So, within a few clicks the correct cutting and folding lines are generated. These lines can be exported to a layered Illustrator file, ready to put graphics on it. This 'Summa version' also has the option to generate an OXF file, immediately ready to be used by GoProduce.

You can download Summa's packaging library via www.summa.com. If you want to enjoy additional packaging features or if you need support on the packaging library, please contact TreeDim via support@treedim.com.

Key features

- Ideal entry into the packaging industry
- Easy standard packaging designs



Go to www.summa.com/faq/how-to-use-the-packlib-library for more information

*PLM Packlib is a program from TreeDim known by 'Picador' software.

> Go to: PLM Packlib Information





Axis Control[™]

Axis ControlTM software gives you full control over Summa's cutting table. The optimised design of the touchscreen makes Axis Control the optimum interface for the machine operator.

With the optional wireless controller, the operator is free to move around the table while changing basic settings.

Key features

- · Machine operating software
- Easy calibration of tools
- Optimising vacuum zone



*Summa Axis Control is standard included with every flatbed purchase

Product Registration

Summa recommends users to register their products online. Upon registration of your Summa products, you can activate several features such as the F-Performance, barcode, and so on. Also, in the registration form, you can choose to tick the box if you want to receive our monthly newsletter. This way, you can stay up to date with Summa's latest products and features that might complement your cutting equipment.

All Summa products can be registered through the Summa website.

Inspiring Customer Stories

Customer stories capture an extensive range of end-user experiences. Experiences they gain by operating our Summa cutting equipment daily, week in week out, year in year out. These stories will help you in obtaining a better understanding of the many reasons why a Summa product might just be the gamechanger you were looking for to bring your cutting workflow to the highest possible level.

Customer stories go beyond product leaflets, brochures and other presentations. These real-life views and opinions from people in the field are the actual depiction of a product's benefits as shown in a true production area. So, go ahead and read our blog, which is filled with inspiring customer stories to create innovative and striking applications with our Summa equipment that fits your every cutting need!

Testimonial | CD Design

"THE SUMMA FI612 FLATBED FINISHING SYSTEM SIMPLY OFFERS THE PERFECT SOLUTION TO FINISH THE JOB"

Company: CD Design Glasfolie Core business: Window films Challenge: Accurate & fast cutting Solution: Summa F1612 & F1832 **The Story** | Before the arrival of their first Summa flatbed cutter everything was cut manually or with a Summa D160 roll cutter at CD Design. However, the window film market was growing constantly and the substrates were often too thick to cut with a roll cutter. The purchase of their first flatbed finishing system thus became indispensable very soon. Meanwhile, both an F1612 and an F1832 flatbed cutter are operational - one in each of CD Design's facilities.



/ CD Design Glasfolie about investing in a F1612 & F1832





Go to:

Product Registration





TECHNICAL SPECIFICATIONS

Model	F1612	F1432	F1832
Dimensions	247 x 220 x 110 cm	230 x 422 x 122 cm	279 x 422 x 122 cm
Media Width	Up to 165 cm	Up to 134 cm	Up to 190 cm
Working Area	160 x 120 cm	136 x 320 cm	184 x 320 cm
Vacuum	1.3 kW (50Hz) / 1.75 kW (60Hz)	2.2 kW (50Hz) / 2.55 kW (60Hz)	2 x 2.2 kW (50Hz) / 2 x 2.55 kW (60Hz)
Vacuum Zones	Variable over width of machine	6 zones (2 rows x 3 columns)	8 zones (2 rows x 4 columns)
Requirements	Standard: 3 x 400V + N, 50Hz, max 20A Or: 3 x 208V + N, 60Hz, max 30A Or: 3 x 230V, 50Hz, max 20A	Standard: 3 x 400V + N, 50Hz, max 30A Or: 3 x 208V + N, 60Hz, max 30A Or: 3 x 230V, 50Hz, max 30A	Standard: 3 x 400V + N, 50Hz, max 30A Or: 3 x 208V + N, 60Hz, max 30A Or: 3 x 230V, 50Hz, max 30A

Model	F3220	F3232	All standard solutions incl.
Dimensions	422 x 313 x 122 cm	422 x 422 x 122 cm	 F Series Flatbed System Conveyor System Pneumatic Media Clamps Roll Support Camera System Axis Control Software Drag Module ADC Right ADC Left GoProduce software Speed: up to 1000 mm/sec Acceleration: Up to 1G
Media Width	Up to 332 cm	Up to 332 cm	
Working Area	327 x 210 cm	327 x 320 cm	
Vacuum	4.0 kW (50Hz) / 4.6 kW (60Hz)	2 x 2.2 kW (50Hz) / 2 x 2.55 kW (60Hz)	
Vacuum Zones	7 zones (1 row x 7 columns)	14 zones (2 rows x 7 columns)	
Requirements	Standard: 3 x 400V + N, 50Hz, max 30A Or: 3 x 208V + N, 60Hz, max 30A Or: 3 x 230V, 50Hz, max 30A	Standard: 3 x 400V + N, 50Hz, max 30A Or: 3 x 208V + N, 60Hz, max 30A Or: 3 x 230V, 50Hz, max 30A	



	es: Consumables	ORDER CODE
Drag Module		
391-332	Drag Knife Holder for 36° & 60°	
9TL89-67041	Standard Drag Knives - 36° (5x)	
391-231	Drag Knife - 60o	
391-358	Drag Knife - 55°	
391-360	Drag Knife - 36°	
MP06BK	Fibre Tip Pens - Black (4x)	
395-430	Roller Ball Pens - Black (5x)	
395-431	Roller Ball Pens - Blue (5x)	
395-434	Pen Holders	
Tangential M	odule - Blades	
390-534	Standard Tangential Knife - 36° (5x)	
390-550	Sandblast Tangential Knife - 60°	
390-551	Double Tip Tangential Knife - 36°	
390-560	Tangential Knife 45° Wedge 40/25°	
390-553	Knife Install Tool	
395-348	Nose Piece for 36°	
500-9801	Single Edge Cutout Knife - 65°	
500-9802	Double Edge Cutout Knife - 50°	
500-9803	Double Edge Cutout Knife - 60°	
500-9804	Double Edge Cutout Knife - 50°/ Burr- Free	
500-9807	Burr- Free Heavy-Duty Cutout Knife - 45° / 90°	
500-9807	V-Cut Blade - 0.9 mm (5x)	
500-9825	V-Cut Blade - Hard Metal	
500-3303	Gliding Disk Single Sided Knife	
500-3315	Gliding Disk Double Sided Knife	
500-9890	Perforation Knife 1x1 mm D1.1mm (12TPI)	
500-9891	Perforation Knife 1.7x1.7 mm D1.1mm (8TPI)	
500-9892	Perforation Knife 3x3 mm D4mm (4TPI)	
500-9893	Perforation Knife 5x5 mm D4mm (3TPI)	
Electronic O	scillating Tool / EOT	
500-3313	Knife Guide for EOT	
500-9800	EOT Knife L25 - 65°	
500-9810	EOT Knife L25 - 65° - 80°	
500-9811	EOT Knife L25 - 65° - 85°	
500-9812	EOT Knife L28 - 65° - 85°	
500-9813	EOT Knife L25 - 0° - 65°	
500-9814	EOT Knife L38 - 45° - 86°	
500-9815	EOT Knife L33 - 45° - 85°	
Pneumatic O	scillating Tool POT / POT-L	
500-9830	POT Knife Flat Point L20 T0.63 (3x)	
500-9831	POT Knife Flat Point L27 T0.63 (3x)	
500-9832	POT Knife Flat Point L20 T1.5 (3x)	
500-9833	POT Knife Serrated L27 T1.0 (3x)	
500-9834	POT Knife L20 T1.0 (3x)	
500-9835	POT-L Knife L50 T1.0 (3x)	
High Torque	Rotary Module	
500-9860	Decagonal Knife D25 (3x)	
500-9861	Decagonal Knife D28 (3x)	
500-9862	Decagonal Knife D32 (3x)	
Routing Syst	em	
Routing Syst	em Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x)	
500-9850	Routing Bits D3/3 L38/11 1Fl UC (3x)	
500-9850 500-9852	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x)	
500-9850 500-9852 500-9863 500-9864 500-9854	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/3 L50/06 MP 1Fl UC (3x)	
500-9850 500-9852 500-9863 500-9864 500-9854 500-9856	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/3 L50/06 MP 1Fl UC (3x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x)	
500-9850 500-9852 500-9863 500-9864 500-9854 500-9856 500-9857	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/3 L50/06 MP 1Fl UC (3x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x)	
500-9850 500-9852 500-9863 500-9864 500-9854 500-9856 500-9857 500-9858	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/3 L50/06 MP 1Fl UC (3x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x) HF Routing Bits D6/6 L58/22 MP 1Fl UC BAL (3x)	
500-9850 500-9852 500-9863 500-9864 500-9854 500-9856 500-9857	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/3 L50/06 MP 1Fl UC (3x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x)	
500-9850 500-9852 500-9863 500-9864 500-9854 500-9856 500-9857 500-9858	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/3 L50/06 MP 1Fl UC (3x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x) HF Routing Bits D6/6 L58/22 MP 1Fl UC BAL (3x)	
500-9852 500-9852 500-9863 500-9864 500-9854 500-9857 500-9857 500-9858 500-9858	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/3 L50/06 MP 1Fl UC (3x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x) HF Routing Bit D6/6 L50/14 / POLISHING (1x) Complete bit overview of Summa: www.Summa.com/pdf/summa-router-bits-overview	
500-9852 500-9852 500-9863 500-9864 500-9854 500-9857 500-9858 500-9858 500-9859	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x) HF Routing Bits D6/6 L50/14 / POLISHING (1x) Complete bit overview of Summa: www.Summa.com/pdf/summa-router-bits-overview 3 mm Collet for 1050 Kress	
500-9852 500-9852 500-9863 500-9864 500-9854 500-9858 500-9858 500-9859 500-9859	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x) HF Routing Bits D6/6 L50/14 / POLISHING (1x) Complete bit overview of Summa: www.Summa.com/pdf/summa-router-bits-overview 3 mm Collet for 1050 Kress 4 mm Collet for 1050 Kress	
500-9852 500-9852 500-9863 500-9864 500-9854 500-9857 500-9858 500-9858 500-9859	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x) HF Routing Bits D6/6 L50/14 / POLISHING (1x) Complete bit overview of Summa: www.Summa.com/pdf/summa-router-bits-overview 3 mm Collet for 1050 Kress	
500-9852 500-9853 500-9854 500-9854 500-9856 500-9857 500-9857 500-9858 500-9859	Routing Bits D3/3 L38/11 1FI UC (3x) Routing Bits D4/4 L50/12 1FI UC (3x) Routing Bits D6/10 L50 90° B 2FI (2x) Routing Bits D6/6 L50/22 2 FI UC/DC (2x) HF Routing Bits D6/4 L50/12 MP 1FI UC (3x) HF Routing Bits D6/6 L50/12 MP 1FI UC (3x) HF Routing Bits D6/6 L50/12 MP 1FI UC BAL (3x) HF Routing Bits D6/6 L50/14 / POLISHING (1x) Complete bit overview of Summa: www.Summa.com/pdf/summa-router-bits-overview 3 mm Collet for 1050 Kress 4 mm Collet for 1050 Kress	
500-9852 500-9853 500-9854 500-9854 500-9856 500-9857 500-9858 500-9859 500-9859 500-0241 500-0242 500-0243 500-0243 500-0244 500-9379	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/3 L50/06 MP 1Fl UC (3x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x) HF Routing Bits D6/6 L50/14 / POLISHING (1x) Complete bit overview of Summa: www.Summa.com/pdf/summa-router-bits-overview 3 mm Collet for 1050 Kress 4 mm Collet for 1050 Kress 8 mm Collet for 1050 Kress 8 mm Collet for 1050 Kress	
500-9850 500-9852 500-9863 500-9864 500-9854 500-9857 500-9858 500-9859 500-9859 500-0241 500-0242 500-0243 500-0243 500-0243 500-0244 500-9379	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x) HF Routing Bits D6/6 L50/14 / POLISHING (1x) Complete bit overview of Summa: www.Summa.com/pdf/summa-router-bits-overview 3 mm Collet for 1050 Kress 4 mm Collet for 1050 Kress 6 mm Collet for 1050 Kress 8 mm Collet for 1050 Kress 6 mm Collet for HF Router	
500-9852 500-9853 500-9854 500-9854 500-9856 500-9857 500-9858 500-9859 500-9859 500-0241 500-0242 500-0243 500-0243 500-0244 500-9379	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/3 L50/06 MP 1Fl UC (3x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x) HF Routing Bits D6/6 L50/14 / POLISHING (1x) Complete bit overview of Summa: www.Summa.com/pdf/summa-router-bits-overview 3 mm Collet for 1050 Kress 4 mm Collet for 1050 Kress 8 mm Collet for 1050 Kress 8 mm Collet for 1050 Kress	
500-9852 500-9853 500-9853 500-9854 500-9854 500-9857 500-9857 500-9858 500-9859 500-9859 500-0241 500-0241 500-0242 500-0243 500-0243 500-0243 500-0244 500-9379 Accessories 500-9347 500-9349	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/3 L50/06 MP 1Fl UC (3x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x) HF Routing Bits D6/6 L50/14 / POLISHING (1x) Complete bit overview of Summa: www.Summa.com/pdf/summa-router-bits-overview 3 mm Collet for 1050 Kress 4 mm Collet for 1050 Kress 6 mm Collet for 1050 Kress 6 mm Collet for 1050 Kress 6 mm Collet for HF Router Vacuum Cleaner Bag for Hercules (5x) Filter for Hercules Carbon Filter for Hercules	
500-9850 500-9852 500-9853 500-9854 500-9854 500-9857 500-9857 500-9858 500-9859 500-9859 500-0241 500-0243 500-0243 500-0243 500-0243 500-0244 500-9379 Accessories 500-9348 500-9349 500-9349	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x) HF Routing Bits D6/6 L50/14 / POLISHING (1x) Complete bit overview of Summa: www.Summa.com/pdf/summa-router-bits-overview 3 mm Collet for 1050 Kress 4 mm Collet for 1050 Kress 6 mm Collet for HF Router Vacuum Cleaner Bag for Hercules (5x) Filter for Hercules Carbon Filter for Hercules Vacuum Cleaner Bag for 500-9331 (5x)	
500-9852 500-9853 500-9853 500-9854 500-9854 500-9857 500-9857 500-9858 500-9859 500-9859 500-0241 500-0241 500-0242 500-0243 500-0243 500-0243 500-0244 500-9379 Accessories 500-9347 500-9349	Routing Bits D3/3 L38/11 1Fl UC (3x) Routing Bits D4/4 L50/12 1Fl UC (3x) Routing Bits D6/10 L50 90° B 2Fl (2x) Routing Bits D6/6 L50/22 2 Fl UC/DC (2x) HF Routing Bits D6/3 L50/06 MP 1Fl UC (3x) HF Routing Bits D6/4 L50/12 MP 1Fl UC (3x) HF Routing Bits D6/6 L50/12 MP 1Fl UC BAL (3x) HF Routing Bits D6/6 L50/14 / POLISHING (1x) Complete bit overview of Summa: www.Summa.com/pdf/summa-router-bits-overview 3 mm Collet for 1050 Kress 4 mm Collet for 1050 Kress 6 mm Collet for 1050 Kress 6 mm Collet for 1050 Kress 6 mm Collet for HF Router Vacuum Cleaner Bag for Hercules (5x) Filter for Hercules Carbon Filter for Hercules	

0
ž
Ö
m
ᆋ
0
ö
ŏ
m.
S
_
-

Order codes: Hardware		
F1612-31	Media Handling Add-Ons	
500-9120	Basket	
500-9121 500-9122	Extension Table Roll-up	
500-9140	Conveyor Extension Front	
F1832-31, F32XX-31	Media Handling Add-On	
500-9412 500-9410	Heavy Duty Roll Support (F1832) Heavy Duty Roll Support (F32XX)	
F1432-31,	F1832-31, Miscellaneous Options	
F3220-31	F3232-31	
500-9165 500-9166	500-9155 500-9156	Kit Pump Connection 12m Kit Pump Connection 25m
All F Series	Modules	
500-9300 500-9310	Drag Module Tangential Module	_
500-9361	High Torque Rota	ry Module
500-9330	Routing System (
500-9357 500-9354	Routing System (Routing System (
500-9363	Routing System (I	
500-9362	Routing System (F3232)
500-9372	HF Routing System	
500-9371 500-9373	HF Routing System HF Routing System	
500-9375	HF Routing Syster	
500-9374	HF Routing System (F3232)	
All F Series	Tools for Tangential Module	
500-9311	Kiss Cutting Tool	
500-9312	Single Edge Cutout Tool	
500-9313	Double Edge Cutout Tool	
500-9314 500-9324	Heavy-Duty Cutout Tool Creasing Tool D50 R1.5	
500-9325	Creasing Tool D50 R1.5 Creasing Tool D25 R3 W8 H7	
500-9326	Creasing Tool D25 R1.5 W8 H5.5	
500-9327 500-9328	Creasing Tool D25 R0.75 W1.5 H1.5	
500-9329	Creasing Tool D15 2pt Creasing Tool D15 1pt	
500-9340	V-Cut Tool - 0°	
500-9341	V-Cut Tool - 15°	
500-9342 500-9343	V-Cut Tool - 22.5° V-Cut Tool - 30°	
500-9344	V-Cut Tool - 30° V-Cut Tool - 45°	
500-9315	Perforating Tool	
500-9320 500-9350	Electronic Oscillat Pneumatic Oscilla	
500-9358		ting-Long Tool (POT-L)
All F Series	Mats And Belts	
500-9114	Conveyor Belt Kit (F1612)	
500-9115 500-9333	Protective Mat (F1612) Routing Mat (F1612)	
500-9163	Conveyor Belt Kit (F1330)	
500-9164	Protective Mats (2x) (F1330)	
500-9336 500-9355	Routing Mat (F1330) Conveyor Belt Kit (F1832)	
500-9356	Protective Mat (2x) (F1832)	
500-9333	Routing Mat (F1832)	
500-9181	Conveyor Belt Kit (F3232)	
500-9182 500-9333	Conveyor Belt Kit (F3220) Routing Mat (F3232 / F3220)	
500-5555	Note: Routing Mat for the F3232 / F3220 has to	
	be ordered twice!	
All F Series	Automated Depth Control	
500-9126	Field Upgrade: AI *Requires: ADC Ri	ght
500-9130	Field Upgrade :ADC Left (F1330)* *Requires: ADC Right Field	
500-9135	Upgrade:ADC Left (F1832/F3232)* *Requires: ADC Right	
500-9136	Upgrade:ADC Left (F3220)* *Requires: ADC Right	
All F Series	Accessories	
500-9347	Vacuum Cleaner B	Bag for Hercules (5x)
500-9348	Filter for Hercules	
500-9349 500-9332	Carbon Filter for Hercules	
500-9332 500-9202	Vacuum Cleaner Bag for 500-9331 (5x) Remote Controller Pack	
1NC40-67034	Media Flanges or Core Holders	
Plages contact your dealer for the complete list		

Order codes: Software

All F Series Systems

500-9520	F-Performance Mode (units built before 2018)
500-9511 500-9513	Summa GoProduce™ - Upgrade Summa GoProduce™-Pro Pack
500-9515 500-9516	Summa GoProduce™ - Update Summa GoProduce™ - Lifetime updates
Please contact your dealer for more information	

Please contact your dealer for the complete list

NOTES

NOTES



Professional flatbed finishing systems

Summa nv Rochesterlaan 6 8470 Gistel Belgium Summa America 100 Cummings Center Suite #151-G Beverly MA 01915 USA

www.Summa.com

Follow us on LinkedIn | Facebook | Twitter | YouTube | #SummaFinish

Copyright 2023© Summa nv. Marketing Communications. Summa nv believes that all illustrations and specifications contained in this catalogue are correct at the time of publication. Summa nv reserves the right to make changes at any time, without notice. RevEN23.02 / All rights reserved



